

TECHNICAL DATA

Capacity under lid	11.25L / 3gal		
Pail	PR1125 with Plastic Handle and Tamper Evident Tear Tab		
Lid	LR1125 Lid		
Wall Thickness	PR1125	1.27mm	0.050in
	LR1125	1.35mm	0.053in

Weight (approx.) without bail	PR1125	360g	12.45oz
	LR1125	110g	3.81oz

Material	PR1125	Polypropylene
	LR1125	

Thermal range	0°C (32°F) to 90°C (194°F)
---------------	----------------------------

Decoration	In Mould Labelling
------------	--------------------

Standard Color	Standard in White, other colors available
----------------	---

TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break the Tamper-Evident tab, then remove lid

TO CLOSE: Start the lid at one side first, then apply around while releasing air on opposite side. Pressing the center of the lid if needed to burp container.

RECOMMENDATIONS

Do not double stack skids upon one another; racking recommended. Grade A pallets should be used with boards that have tight spacing to ensure proper box support. Stretch wrapping machine tension should be adjusted to ensure no deformation of the boxes. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

PRODUCT CODE

PAIL: PR1125

LID: LR1125



DIMENSIONS	CM	INCHES
Pail Height	25.43	10.01
Pail Height with Lid	25.60	10.08
Upper width with Lid	29.16	11.48
Lower Width	23.88	9.4

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
PR1125 240 per pallet
LR1125 1920 per pallet (80 per box)
- Max 2 pallets high for warehousing of Pails
- Max 2 pallets high for warehousing of Lids

