

# 513

## UTILITY PAPER MASKING TAPE

## INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

### DESCRIPTION

Beige crepe paper masking tape coated with an aggressive pressure-sensitive natural rubber adhesive. Designed primarily as an all-purpose product for non-critical applications.

### PRODUCT APPLICATION

Interior paint masking, textile, carpet seaming, silk screening, mail rooms, golf club shaft (build-up), school bids, and for light-duty bundling, packaging, industrial, manufacturing, splicing and tabbing.

### GOVERNMENT COMPLIANCE

Product qualified to meet ASTM D6123 specifications.

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

<b>Backing</b>	Crepe Paper
<b>Adhesive</b>	Natural/Synthetic Rubber
<b>Adhesion to Steel</b> (oz/in of width) PSTC-1	36 (9.8 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-31	19 (83.2 N/25mm)
<b>Elongation</b> (at break) PSTC-31	6.4%
<b>Total Thickness</b> (mils) PSTC-33	5.0 (0.127mm)
<b>Quick Stick to Steel</b> (oz/in of width) PSTC-5	12 (3.3 N/25mm)
<b>Temperature Resistance</b>	+50°F ~ +180°F (+10°C ~ +82°C)
<b>Color</b>	Beige



3647 Cortez Road West | Bradenton, FL 34210 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.



EFFECTIVE: 02/11