

PG49

HIGH TEMP PREMIUM PAPER MASKING TAPE

DESCRIPTION

A beige, smooth crepe, masking tape with pressure-sensitive natural rubber/resin adhesive. Designed for paint masking requiring clean and easy removal from a variety of surfaces. Resists paint flaking and has good quick stick and holding properties. Can be exposed to oven temperatures up to 325°F (163°C) for 30 minutes.

PRODUCT APPLICATION

Automotive, truck, bus and marine paint masking. Recommended hot to warm removal, but can be removed cold.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

| | |
|---|----------------------|
| Backing | Smooth Crepe Paper |
| Adhesive | Natural Rubber/Resin |
| Adhesion to Steel (oz/in of width) | 24 (6.5 N/25mm) |
| Tensile Strength (lbs/in of width) | 24 (105 N/25mm) |
| Elongation (% at break) | 11 |
| Total Thickness (mils) | 6.7 (0.17mm) |
| Quick Stick (oz/in of width) | |
| To Kraft | 5 (1.4 N/25mm) |
| To Steel | 13 (3.5 N/25mm) |
| Color | Beige |

