

PG56

MEDIUM TEMP MEDIUM GRADE PAPER MASKING TAPE

DESCRIPTION

A beige, high temperature, medium crepe, paper masking tape with pressure-sensitive natural rubber adhesive. Can withstand exposure to forced drying conditions up to 250°F (121°C) for 30 minutes with warm to hot removal recommended. Excellent quick-stick and holding properties. Designed for applications requiring transfer resistance in conjunction with a variety of paints and surfaces. Special release coat provides an extra measure of moisture and solvent resistance. Not recommended for outdoor exposure.

PRODUCT APPLICATION

Interior paint masking, spray painting (air-dry) autos, boats, etc., boat manufacturing (fiberglass), silk screening, mail rooms, marble manufacturing (man-made), golf club shaft (build-up), carpet pad / pad splicing, freezer tape, and light bundling, packaging, splicing and tabbing.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Medium Crepe Paper
Adhesive	Natural Rubber/Resin
Adhesion to Steel (oz/in of width)	33 (9 N/25mm)
Tensile Strength (lbs/in of width)	26 (114 N/25mm)
Elongation (% at break)	9
Total Thickness (mils)	6.4 (0.162mm)
Quick Stick (oz/in of width)	
To Kraft	9 (2.5 N/25mm)
To Steel	17 (4.7 N/25mm)
Operating Temperature Range	40°F ~ 250°F (4.4°C ~ 121°C)
Color	Beige

