

AC74 Carpet Tape

DOUBLE-COATED CLOTH TAPE

DESCRIPTION

Woven cloth coated on both sides with pressure-sensitive rubber adhesive that provides moderate adhesion and good initial tack to a variety of surfaces (including irregular and porous surfaces). The adhesive is formulated for clean, low residue removal from most surfaces. Features an easy release PE film liner (white).

Product is not repulpable.

PRODUCT APPLICATION

Temporary mounting, splicing, carpet tape (hold-down and position), manufacturing and engravers (temporary holding) and any application that requires the joining of two surfaces.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 04/16

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

| | |
|---|------------------|
| Backing | Woven Cloth |
| Adhesive | Natural Rubber |
| Adhesion to Steel (oz/in of width) PSTC-101 | |
| Exposed Side | 50 (13.7 N/25mm) |
| Lined Side | 50 (13.7 N/25mm) |
| Tensile Strength (lbs/in of width) PSTC-131 | 42 (184 N/25mm) |
| Total Thickness w/o Liner (mils) PSTC-133 | 12.0 (0.30mm) |
| Liner Type and Color | PE film – White |
| Tape Color | Natural |

