



## **Applications:**

Remove any surface dirt or dust with a treated mop. Wash floor with a neutral detergent. Dilute with unheated tap water according to the dilution rates listed below.

Mop-on application: Apply with a clean mop daily to enhance the gloss and preserve the finish in traffic areas.

Auto-scrubbers: Fill scrubber reservoir. Regulate the flow of the solution at a low, steady rate. Apply just enough pressure on the pad assembly to touch the surface of the floor. The rejuvenated area will be ready for traffic in minutes after cleaning. Rinse the automatic scrubber tank thoroughly with water after use to prevent film build-up.

Routinely, apply with a clean mop. Allow the solution to dry for 30 minutes before dry burnishing with

#### Dry burnishing:

### **Benefits:**

- Extends the life of flo
- Increases slip resistar
- Built in detergents to
- Removes scuff and b
- Safe for all types of flo
- Restores shine to elin frequent refinishing

#### Codes:

# Product Code:

• UPC:

UHS buffing pad.

## **Specifications:**

Colour	White
DIN	No
Odour	Acrylic
рН	8.2 - 8.8
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	Yes
Food Safe	No
Kosher	Yes
COF Shelf Life	0.6
	Up to 3 years after manufacturing
	OdourpHViscositySolventPhosphatesWHMISECOLOGOFood SafeKosherCOF



